

INSTRUCTIONS

This really isn't rocket science, so we will not over-complicate the instructions for you.....or maybe we will muahahaha:

Setting up the Frame:

- 1) Carefully remove contents from the box, and set the 2 main frame pieces on their base. For the rear seat mount frame make sure the side with the holes is facing towards the front main frame. Place flat washer on each longer bolt, slide them thru the two frames, slide the spring washer on each end and then tighten down the nuts.
- 2) insert the steering wheel mount into it's mounting posts and 2 tightening knobs into the hex bolts near the top of the mounting posts
- 3) insert the "L" shaped keyboard mount arm into it's mounting post, and then slide the keyboard tray onto the square end of the arm.
- 4) if you want to run the monitor stand then insert it into it's mounting posts located on the steering mount mounting posts, and secure them with 2 tightening knobs. The stand has been tested up to a 19" LCD monitor. Anything larger may need some taping to secure the monitor.

Box Contents

Frame:

- 1ea Front main frame
- 1ea Rear main frame (seat mount)
- 1ea Shifter mount
- 1ea Steering mount
- 1ea monitor stand
- 1ea keyboard/mouse tray
- 1ea "L" shaped mounting arm
- 1ea Obutto racing seat

Hardware: located in small box

- 4ea seat mount bolts (the shorter ones)
- 3ea frame carriage bolts (the longer ones)
- 7ea spring washers
- 7ea flat washers
- 7ea nuts
- 5ea tightening knobs (4ea for the frame and 1ea for the shifter mount)

Mounting the Seat:

Please note, the seat mount holes are long to adjust the seat location for different sized people, attach the seat forward if you are 5ft 7in and under, and attach the seat towards the rear if you are over 5ft 7in

****CAUTION - do not put your fingers into the sliders as it could harm you****

- 1) Locate the 4 shorter bolts, slide them thru the bottom of the seat sliders, 1 on each side of the front of the sliders, and 1 on each side in the last hole on the rear of the sliders. You may have to adjust the sliders to get access to the above mentioned holes. Just pull the seat lever up and manually move the sliders.
- 2) To mount the seat to the frame first make sure the seat sliders are at equal lengths, then hold the seat over the mounting holes, according to your height, and lower the seat until all 4 bolts slot through the mounting holes
- 3) secure the bolts with the nuts and washers in this order....flat washer, spring washer, nut

Now that was easy.....right??!! :) ENJOY your **oZone** cockpit!!

Warranty Info:

-Obutto will replace parts free of charge within 6 months of purchase, excluding shipping fees, that are broken from normal use of the cockpit. Pictures are required with an explanation of how the piece was broken.

Liability Statement:

Obutto is not responsible for any harm to persons or hardware/software.